



PJ19 11.6" Rugged Tablets

Slim, Rugged, Multi-functional Wireless Computing

The PJ19 Series Rugged Tablets feature the integration of high brightness 11.6" capacitive touch screens and high performance, energy-efficient Intel® processors within slim, lightweight, durable packages. With built-in smart card/CAC reader, Wi-Fi and Bluetooth as well as options for front/ back cameras, barcode scanner, GNSS, and 4G connection, these robust tablets offer seamless information capture and transmission for improved workflow. Rated IP65 and MIL-STD-810G certified with wide temperature range (-4°F to 140°F), the PJ19 Series Rugged Tablets provide reliable operation in harsh, mission-critical environments.





Features

- 11.6" high-brightness capacitive touch screen (800 nits), digital pen support
- Intel® 8th Generation Core™ i5/i7 processor
- Microsoft® Windows® 10 IoT Enterprise operating system
- NIST compliant BIOS available
- High capacity, hot-swappable battery pack
- IP65 rated, MIL-STD-810G and MIL-STD-461F certified
- Build-in smart card/ CAC reade

Major Options

- RS-232 port
- Front and back cameras
- · Barcode scanner
- U-blox M8 GNSS module
- · 4G LTE/AWS

Specifications

System

| СРИ | Intel® |
|----------------------------|---|
| RAM | 8GB to 16GB |
| Storage | 256GB to 2TB Flash |
| Operating System | Microsoft® Windows® 10 IoT Enterprise |
| NIST Compliance | NIST compliant BIOS available |
| Display | 11.6" LED-backlight screen with capacitive touch |
| Display Resolution | 1920 x 1080 |
| Fan/ Fanless | Fanless |
| Control Switch and Buttons | 1 power button, 1 trigger button, 3 programmable buttons, 1 RF switch |
| Indicator | 1 power/ battery status LED |
| Microphone | Built-in microphone with DSP for real-time video |
| Speaker | Built-in speaker |

Network Interface

Reader

| WLAN | Wi-Fi 802.11ac, 2.4GHz/ 5GHz dual band |
|-----------|---|
| Bluetooth | Bluetooth 4.2 LE |
| I/O Ports | |
| USB Ports | 1 USB 3.0 and 1 USB 2.0, or can be changed to 1 USB 3.0 and 1 full size SD card slot |

Headset Jack 1 (3.5mm) DC-in 1 Ethernet 1 RJ45 connector for Ethernet Smart Card/CAC Full-slot, reads ISO 7816 T=0, T=1; 1.8/3/5V smart card

Mechanical and Environmental

| AC/DC Adapter | Input: 100-240V AC; Output: 19V DC, 3.42A |
|---------------------------|--|
| Battery Pack | Hot swappable battery, 11.4V, 5400mAh; Hot swappable battery, 11.4V, 8000mAh (optional) |
| Enclosure | ABS + PC plastics and magnesium-aluminum alloy |
| Protective Bumpers | Rubber bumpers on each corner for handling protection |
| Dimensions (H x W x D) | 8.3 x 12.4 x 0.86 in/ 212 x 316 x 21.9 mm |
| Weight | 3.5 lbs/ 1.6 kg |
| Durability | IP65, MIL-STD-810G and MIL-STD-461F certified |
| Regulatory | FCC Class B, CE, RoHS compliant |
| Temperature | Operation*: -20°C to 60°C (-4°F to 140°F), tested under MIL-STD-810G method 501.6, Procedure II, and method 502.6, Procedure II * For battery safety, optimal functionality and performance, the recommended usage temperature range is from -10°C to 45°C (14°F to 113°F). Storage: -55°C to 70°C (-67°F to 158°F) |
| Humidity | 0% – 90% non-condensing |

Major Options

| Barcode Scanner | 2D scanner, reads 1D also |
|------------------|---|
| Camera | 2 megapixel front camera, and 8 megapixel back camera |
| GNSS Module | U-blox M8 GNSS module with concurrent reception of GPS and GLONASS; industry leading -167dBm navigation sensitivity |
| I/O Port Module | RS-232 port, 6-pin lockable connector included |
| Mobile Broadband | 4G LTE/AWS |

* Specifications subject to change without notice.

Accessories

| Digital Pen | |
|-------------|--|
| Pen Tip | Diameter: 0.059 in/ 1.5mm, replaceable |
| Buttons | 2 side buttons (right-click and eraser) |
| Battery | 1 AAAA, replaceable |
| Color | Black |
| Dimensions | Length: 5.5 in/ 140 mm (including pen tip) Diameter: 0.38 in/ 9.7 mm |
| Weight | 0.055 lbs/ 25 g |

Desktop Charging Cradle

Docking support with ports for Power, USB, HDMI outputs and Ethernet



Detachable Keyboard

Designed to connect to a DT Research Tablet, instantly pairs, ideal for 2-in-1 applications.



Tablet Mount Cradle

Offers Tablet storage and security with power, HDMI-out, COM, Ethernet pass-through, and USB ports. Power supply is not included



5-Bay Cabinet Charger

Multi-tray charger, capable of charging up to 5 tablets simultaneously



Battery Charging Kits



· Carrying Case







