



PM810MD / PM813MD RUGGED 2-IN-1 MEDICAL TABLETS

Slim, Anti-microbial, UL60601-1 Certified Tablet for Efficient Operations

The Peace Maker Tech's Rugged 2-in-1 Medical Tablets feature the integration of brilliant capacitive touch screens and high performance, energy-efficient Intel® Core™ i series processors within slim, lightweight, durable packages. With built-in front and back cameras, Wi-Fi, Bluetooth as well as optional data capture modules, these medical tablets offer health professionals effective tools to monitor, record and retrieve patient information.





Features

- 10.1" or 13.3" multi-touch screen, 1000 nits, digital pen support
- Intel[®] 8th Generation Core[™] i processor
- Microsoft® Windows® 10 IoT Enterprise or Ubuntu operating system
- Docking keyboard option for 2-in-1 (tablet/ laptop) applications
- UL60601-1 certified with anti-microbial enclosure
- IP65 and MIL-STD-810G certified
- NIST compliant BIOS available
- Hot swappable battery pack
- Built-in front and back cameras
- Built-in smart card/CAC reader

Major Options

- Barcode scanner
- · Single/dual frequency NFC/RFID reader
- 4G LTE/AWS

Specifications





| Model | PM810MD | PM813MD |
|--------------------|---|---|
| System | | |
| RAM | 8GB to 16GB | 8GB to 16GB |
| Storage | 256GB to 512GB Flash | 256GB to 512GB Flash |
| Operating System | Microsoft® Windows® 10 IoT Enterprise or Ubuntu | |
| NIST Compliance | NIST compliant BIOS available | |
| Display | 10.1" LED-backlight, high-brightness (1000 nits) screen with capacitive touch, outdoor viewable | 13.3" LED-backlight, high-brightness (1000 nits) screen with capacitive touch, outdoor viewable |
| Display Resolution | 1920 x 1200 | 1920 x 1080 |
| Buttons | 1 power button, 2 brightness control buttons, 5 programmable buttons | 1 power button, 2 brightness control buttons, 5 programmable buttons |
| Speaker | Built-in speaker | Built-in speaker |
| Camera | Full-HD front camera and 8 megapixel back camera | Full-HD front camera and 8 megapixel back camera |
| N | | |

Network Interface

WLAN

| Bluetooth | Bluetooth 4.2 LE | Bluetooth 4.2 LE |
|------------------------|---|--|
| I/O Ports | | |
| USB Ports | USB 3.0×1 , USB Type C $\times 1$ (data transmitting and charging) | USB 3.0 x 3, USB Type C x 1 (data transmitting and charging) |
| Headset Jack | 1 (3.5mm) | 1 (3.5mm) |
| Ethernet Port | Ethernet 10/ 100/ 1000MB Base-T LAN | Ethernet 10/ 100/ 1000MB Base-T LAN |
| Smart Card/ CAC Reader | Full-slot reads ISO 7816 T=0 T=1: 1 8/3/5V smart card | Full-slot reads ISO 7816 T=0 T=1: 1 8/3/5V smart card |

Wi-Fi 802.11ac, 2.4GHz/5GHz dual band

Mechanical and Environmental

| AC/DC Adapter | Input: 100-240V AC; Output: 20V DC, 3A | | |
|------------------------|---|---|--|
| Battery Pack | Hot swappable battery, 11.4V, 5400mAh | Hot swappable battery, 11.4V, 5400mAh | |
| Enclosure | ABS + PC plastics and magnesium-aluminum alloy; anti-microbial enclosure | | |
| Dimensions (H x W x D) | 7.8 x 11 x 0.86 in/ 198 x 280 x 21.9 mm | 10.1 x 13.2 x 0.8 in/ 256 x 335 x 21 mm | |
| Weight | 3.1 lbs/ 1.4 kg | 3.97 lbs/ 1.8 kg | |
| Durability | IP65 and MIL-STD-810G certified | IP65 and MIL-STD-810G certified | |
| Regulatory | FCC Class B, UL60601-1, CE, RoHS compliant | | |
| Temperature | Operation: -10°C to 60°C (-14°F to 140°F), optional -30°C to 60°C (-22°F to 140°F) Storage: -55°C to 70°C (-67°F to 158°F) | | |
| Humidity | 0% – 90% non-condensing | | |

Major Options

| Barcode Scanner | 2D scanner, reads 1D also | 2D scanner, reads 1D also |
|------------------|---|--|
| NFC/RFID Reader | HF 13.56MHz, ISO standard 15693, 14443A(B) & 18000-3 mode-1 | Dual frequency, reads both 125KHz and 13.56MHz credentials |
| Mobile Broadband | 4G LTE/AWS | 4G LTE/AWS |

^{*} Specifications subject to change without notice.

Accessories

























